# IDENTITY GROUP INTERIOR SIGN SOLUTIONS CLEARCRYL™ SAMPLE SPEC SHEET- SIGNAGE AND GRAPHICS



### PART 1 GENERAL

## 1.1 SECTION INCLUDES

- A. Interior signage of the following types:
  - 1. Clearcyrl™

### **1.2 RELATED SECTIONS**

- A. Section 10410 Directories
- B. Section 10420 Plaques
- C. Section 10430 Exterior Signage

#### 1.3 REFERENCES

- A. ICC/ANSI A117.1 Accessible and Useable Buildings and Facilities
- B. USATBCB Americans with Disabilities Act (ADA), Accessibility Guidelines for Buildings and Facilities (ADAAG)

# 1.4 SUBMITTALS

- A. Submit under provisions of Section 01300
- B. Product Data: Manufacturer's descriptive literature
- C. Shop Drawings: List sign styles, lettering, locations and dimensions of each interior sign
- D. Selection Samples: One complete set of color chips representing manufacturer's full range of available colors
- E. Verification Samples: Two full size samples, representing type, style and color specified including method of attachment

# **1.5 QUALITY ASSURANCE**

A. Regulatory Requirements: Comply with requirements of ICC/ANSI A117.1 and ADAAG

# 1.6 DELIVERY, STORAGE, AND HANDLING

A. Inspect products upon receipt. Store products in manufacturer's packaging until ready for installation

### 1.7 PROJECT CONDITIONS

A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results

### **PART 2 PRODUCTS**

### 2.1 MANUFACTURERS

A. Acceptable Manufacturer: IDENTITY GROUP

1480 Gould Dr., Cookeville, TN 38506

TEL: (931) 432-4000 FAX: (931) 432-6477

Website: www.identitygroup.com

B. Substitutions: Not permitted

C. Requests for substitutions will be considered in accordance with provisions of Section 01600.

#### 2.2 SIGNS

A. ADA-Compliant Interior Signage, Custom Design:

#### 2.3 INTERIOR SIGNAGE SCHEDULE

A. Manufacturer's standard monolithic thermally formed and bonded tactile plaque constructed utilizing a high-pressure thermoforming process, which provides a fully homogeneous plaque sign. The sign body, face, raised text and Braille are compression molded to form a single dimensional component creating a sign surface, body, and graphic elements which exhibit toughness to scratching, cracking, gouging and graffiti. Molded surface is available in manufacturer's three surface textures.

- 1. <u>Style</u>: Custom Clearcyrl™ Sign by Alchemy Dimensional Graphics, LLC
- 2. Material: Extruded clear acrylic, cell cast clear and tinted acrylic.
- 3. <u>Sign Thickness</u>: 1/8 inch (3mm)-1/4 inch (6mm)-3/8 inch (10mm)-1/2in(12mm)

- 4. Tactile Characters/Symbols: Raised at least .045" from sign plate face
- 5. Construction One-piece; adhered or engraved characters not acceptable
- 6. <u>Lettering Style</u>: Typeface and letter size per current ADA guidelines.
- 7. Braille: Grade 2 ADA compliant Braille positioned per ADA guidelines.
- 8. <u>Contrast</u>: Letters, numbers, and symbols shall contrast with background per ADA guidelines.
- 9. Bevel Options: Classic, Bull Nose, Chamfered
- 10. <u>Profiles</u>: Options: Laser or Router cut. Manufacturer's full range of standard shapes and or custom.
- 11. <u>Text Options;</u> Integral Alchemy Metals; Nickel, Aluminum, Bronze, Faux Gold, Copper, Tool Steel, Brass. Integral Alchemy color, or UV ink tipped Colors chosen from Pantone or other standard paint colors.
- 12. Surface Texture: Smooth, Stipple or Slate

#### PART 3 EXECUTION

#### 3.1 EXAMINATION

- A. Examine installation areas to ensure that conditions are suitable for installation
- B. Examine signage for defects prior to installation. Do not install damaged signage

### 3.2 PREPARATION

- A. Verify mounting heights and locations for interior signage will comply with referenced standards
- B. Clean mounting locations of dirt, dust, grease or similar conditions that would prevent proper installation

#### 3.3 INSTALLATION

A. Install signs level, plumb, without distortion, and in proper relationship with adjacent surfaces using manufacturer's recommended standard mounting system.

- B. Removed adhesive from exposed sign surfaces as recommended by manufacturer
- C. Clean signs after installation as recommended by manufacturer
- D. Replace damaged products before Substantial Completion

# 3.4 INTERIOR SIGNAGE SCHEDULE

A. Refer to the list of interior signs required for the project as attached to this section.

**END OF SECTION**