

IDENTITY GROUP INTERIOR SIGN SOLUTIONS
NATURALS SAMPLE SPEC SHEET--
SIGNAGE AND GRAPHICS



PART 1 GENERAL

1.1 SECTION INCLUDES

A. Interior signage of the following types:

1. Naturals

1.2 RELATED SECTIONS

A. Section 10410 – Directories

B. Section 10420 – Plaques

C. Section 10430 – Exterior Signage

1.3 REFERENCES

A. ICC/ANSI A117.1 – Accessible and Useable Buildings and Facilities

B. USATBCB – Americans with Disabilities Act (ADA), Accessibility Guidelines for Buildings and Facilities (ADAAG)

1.4 SUBMITTALS

A. Submit under provisions of Section 01300

B. Product Data: Manufacturer's descriptive literature

C. Shop Drawings: List sign types, lettering, locations and dimensions of each interior sign

D. Selection Samples: Samples available on request.

E. Verification Samples: Two full size samples, representing type, style and color specified including method of attachment

1.5 QUALITY ASSURANCE

A. Regulatory Requirements: Comply with requirements of ICC/ANSI A117.1 and ADAAG

1.6 DELIVERY, STORAGE, AND HANDLING

A. Inspect products upon receipt. Store products in manufacturer's packaging until ready for installation

1.7 PROJECT CONDITIONS

A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: IDENTITY GROUP, LLC;
1480 Gould Dr., Cookeville, TN 38506
TEL: (931) 432-4000 FAX: (931) 432-6477
Email: interiorsigns@identitygroup.com
Website: www.identitygroup.com
- B. Substitutions: Not permitted
- C. Requests for substitutions will be considered in accordance with provisions of Section 01600.

2.2 SIGNS

- A. ADA-Compliant Interior Signage, Custom Design:

2.3 INTERIOR SIGNAGE SCHEDULE

A. Manufacturer's standard tactile plaque constructed utilizing a proprietary pressure forming process which creates signs densified organic wood and wood fiber based products, with thermally fused acrylic first surface and graphics. Construction is balanced with a thermally embedded 2nd surface. The sign body, face, raised text and Braille are compression molded to form a single dimensional component that results in a sign surface that exhibits a toughness that resists scratching, cracking, gouging and graffiti. Molded surface is available in manufacturer's three surface textures.

1. Style: Custom Organic Sign by Alchemy Dimensional Graphics, LLC
2. Material: Wood Veneer faced MDF(FCS certified materials) – Bamboo plywood – MDF(FCS certified)
3. Sign Thickness: 3/16" (4.5mm) nominal.
4. Tactile Characters/Symbols: Raised .045" (1mm) from sign face
5. Construction: Proprietary thermally bonded construction. (no Glue – no VOC based finishes)
6. Lettering Style: Typeface and letter size per ADA compliant fonts

7. Braille: Grade 2 ADA compliant Braille positioned per ADA guidelines.
8. Contrast: Letters, numbers, and symbols shall contrast with background per ADA guidelines.
9. Bevel Options: Classic, Bull Nose, Chamfered
10. Profiles: Options: Laser or Router cut. Manufacturer's full range of standard shapes and or custom.
11. Background Color: Colors chosen from Pantone or other standard paint colors, surface applied.
12. Text Options; Integral Alchemy Metals; Nickel, Aluminum, Bronze, Faux Gold, Copper, Tool Steel, Brass. Integral Alchemy color, or UV ink tipped Colors chosen from Pantone or other standard paint colors.
13. Surface Texture: Smooth, Stipple or Slate

PART 3 EXECUTION

3.1 EXAMINATION

- A. Examine installation areas to ensure that conditions are suitable for installation
- B. Examine signage for defects prior to installation. Do not install damaged signage

3.2 PREPARATION

- A. Verify mounting heights and locations for interior signage will comply with referenced standards
- B. Clean mounting locations of dirt, dust, grease or similar conditions that would prevent proper installation

3.3 INSTALLATION

- A. Install signs level, plumb, without distortion, and in proper relationship with adjacent surfaces using manufacturer's recommended standard mounting system
- B. Removed adhesive from exposed sign surfaces as recommended by manufacturer
- C. Clean signs after installation as recommended by manufacturer
- D. Replace damaged products before Substantial Completion

3.4 INTERIOR SIGNAGE SCHEDULE

- A. Refer to the list of interior signs required for the project as attached to this section

END OF SECTION